





AQA drink COOLER



WATER DISPENSERS FOR THOSE WHO WANT TO MAXIMISE THE SPACE ON THE TOP

BWT AQA drink COOLER is the complete range of water dispensers that, thanks to their compact dimensions and the fact that they can be installed under the sink, leave you plenty of free space on the counter.

The small dimensions allow the dispensers to be easily positioned without impacting on the aesthetics of your venue.

They fit inside the kitchen cabinets, together with the filter and CO2 cylinder, and they can be connected to the matching column and drip trav.

The AQA drink COOLER range includes a wide selection of professional water coolers, robust and reliable over time, which meet the highest quality standards for performance and product quality.

- → Ideal for bars, restaurants, canteens
- → 2 or 3 water options: ambient and cold or ambient, cold and sparkling
- → Capacity: 50 to 120 l/h (higher capacities available upon demand)

It's possible to combine BWT's AQA drink mineralization and filtration solutions, so that you have valuable water rich in valuable minerals. In addition, periodic disinfection and cleaning can be performed using BWT's EasyCare system.

The dispenser needs to be combined with one or more dispensing towers with taps.

- → ICE BANK SYSTEM
- → SAVING SPACE ON THE COUNTER
- → STURDY AND FUNCTIONAL DESIGN









1	
	NECTED* CONNECT

Item n° – WD	125591238	125591232	125591239	125591233	125591240	125591234		
C – Cold	✓	✓	✓	✓	✓	✓		
A - Ambient	✓	✓	✓	✓	✓	✓		
S – Sparkling	-	✓	-	✓	-	✓		
H - Hot	-		-		-			
Cooling capacity I/h (Δt= 10°C)	5	0	80		120			
Number of people (approx.)	20/50		50/80		80/120			
Cooling technology	Ice bank							
Cooling control	-2 °C to +7 °C Thermostat							
Recirculation pump/stirrer	- Opti				ional			
Compressor power	185 W		245 W		380 W			
Refrigerant	R290							
Carbonator capacity	1,6		1,4		1,4			
Power supply	230 V / 50-60 Hz							
Maximum power consumption	220 W		300 W		500 W			
Pump type	Booster 220V 135 PSI					200 l/h motor 150 W		
Ø water inlet pipe	8 mm							
Ø CO2 in l et pipe	6 mm							
Maximum CO2 inlet pressure	4 bar							
Water inlet pressure (min./max.)	1,5 / 3,5 bar							
Dimensions WD (WxDxH) mm	180×46	50×430	270×4	50×440	300×5	10×400		
Weight kg (approx.)	1	8	2	21	2	:5		
Material of construction	Stainless steel							
Water selection point	To be combined with dispensing tower							

BWT AQA drink COOLER dispensers are characterised by their small dimensions and minimalist design.

They convey a robust and clean feel. Surfaces can be easily sanitised.

TECHNICAL FEATURES

Water cooling technology using an ice bank system guarantees cold and sparkling water in large quantities with low energy consumption.

The water is dispensed via the matching dispensing tower.

INSTALLATION

The installation is very easy: a simple connection to the water mains, electricity and dispensing tower * (to be purchased separately, see next pages) using the supplied kit is all that is

Quick connections are positioned on the front of the dispenser.



*Dispensing tower (AQA drink DIGI TOWER or AQA drink TOWER) must be purchased separately

PRODUCT PORTFOLIO BE THE CHANGE

^{*} Connectivity via b.Connect possible for devices up to 60 l/h